



## 3" 4" 5" 6" 8" 10" 12" Stainless Steel Camlock Coupling

Our Product Introduction

### Basic Information

- Place of Origin: CHINA
- Brand Name: DEYE
- Certification: ISO9001:2015 PED
- Model Number: DY-QC-01
- Minimum Order Quantity: 10PCS
- Price: USD2-USD25 each
- Packaging Details: carton box+ ply wooden cases or carton+ Pallets
- Delivery Time: 20 days for usual order, 7 days for stocked items
- Payment Terms: T/T, L/C, D/P
- Supply Ability: 1000pcs one month



### Product Specification

- Highlight: 12in stainless steel camlock coupling,  
10in stainless steel camlock coupling,  
4in stainless steel camlock fittings

for more products please visit us on [piping-industry.com](http://piping-industry.com)

## Product Description

### 3" 4" 5" 6" 8" 10" 12" Stainless Steel Camlock Coupling

Camlock couplings are well-known as quick hose coupling providing quick connection and disconnection for pumps, tanks, equipment, Stainless steel cam lock fittings allow for quick and secure hose connections. The camlock couplings mate by inserting the grooved coupling into the cam coupling and simply closing the cam or lever arms. Safety pins or locks prevent the cam arms from accidental disconnection during use.


#### Product Information/Product Description/Basis Information/Specification

Name	Camlock Quick Coupling
Material	stainless steel ANSI 304,316,304L,316, Aluminum, Brass, PP
Size	1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8" 10" 12"
Thread	Thread BSP, BSPT, NPT, DIN259/2999
Type	A, B, C, D, E, F, DC, DP (A, B, D, F with thread, B, C, D, DC with handles)
	Type "A", has a male grooved adapter and a female pipe thread (BSP or NPT thread) of the same size
	Type "B", has a female camlock end and a male pipe thread of the same size
	Type "C", has a female camlock on one end and a male hose tail on the other
	Type "D", has a female camlock end and a female pipe thread of the same size
	Type "E", has a male camlock on one end and a male hose tail on the other
	Type "F", has a male grooved adaptor and a male pipe thread of the same size
Gaskets	NBR, EPDM, Viton, PTFE gasket are all available
Cam levers	We use stainless steel cam levers
Pressure	3/4"-2" 250PSI (17.6bar),3"-4" 200PSI (14.8bar)
	2 1/2" 225PSI (15.8bar),6" 150PSI (10.5bar)
Technology	Investment casting. Precision casting, NC machine
Packing	pcs/polybag, polybag/carton, cartons/pallet or according to your requirement
Certificate	ISO9001:2015
Process	CNC machine, Testing equipment

#### Features /Advantages:

- 1.Simple structure, convenient operation, quick connect and open it.
- 2.compact size, light weight, good sealing and interchangeability.
- 3.Adapt to all kinds of working conditions, widely used in liquid, powder and other medium.
- 4.Joint connected with taper pipe threads, outside taper pipe threads, intubation connection, flange connection, etc.
5. Cam & groove couplings are easy to operate. Camlock consists of two parts - male adapter and female coupler. You just need insert the adapter into the coupler until contact is made with the gasket. Then press down the cam arms simultaneously to produce a uniform gasket compression. During the process of installation, no tools are required and hand pressure is enough. Hence, camlock fittings not only save your time but also the tools and human power.
6. Cam & groove couplings are equipped with PVC suction hoses, lay flat discharge hoses and other low-pressure hoses. It can simplify the operation and save working time greatly. However, cam locks are not suitable for any kind of hose. It is forbidden to be used in compressed air or gas or high-pressure applications.

#### Types of the cam & groove couplings

<b>Type A</b> <b>Male Adapter X Female</b>	<b>Type B</b> <b>Female Coupler x Male</b>
	
<b>Type C</b> <b>Female Coupler X hose Shank</b>	<b>Type D</b> <b>Female Coupler x Female</b>
	
<b>Type E</b> <b>Male Coupler X Hose Shank</b>	<b>Type F</b> <b>Male Adapter xMale</b>
	
<b>Type DC</b> <b>Dust Cap</b>	<b>Type DP</b> <b>Dust Plug</b>
	

#### **Application and usage**

Quick release coupling for low-pressure systems, Suitable for Construction; Fire hydrant; Garden; Farming

#### **Our Service**

1. Technical support
2. Raw Material Quality control.
3. Inspection during the production time.
4. Final Test includes Surface, Dimension, PT Test, RT test, ultrasonic Test
5. Test Report each shipment
4. Flexible Delivery terms. EXW FOB CIF CFR DDP DDU
5. Flexible payment Ways: LC. TT. DP
6. Customized Package includes Logo. Cases Dimension.
7. 18 months quality Guarantee time.
9. Free replacement by air if any error founded
10. 24 hours to Feedback your questions

**DEYE** SHIJIAZHUANG DEYE PIPING INDUSTRY CO., LTD Pipefittings Department)

+8613292824811

sales@deyepiping.com

pip-ing-industry.com

No. 368 Youyi St. Shijiazhuang, Hebei, China