



GGG50 GGG40 Cast Ductile Iron Swing Check Valves With Arm Lever Weight

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: DEYE
- Certification: ISO9001:2015 PED
- Model Number: DY-CV-W-06
- Minimum Order Quantity: 10PCS
- Price: USD2-USD20000 each
- Packaging Details: carton box+ ply wooden cases or carton+ Pallets
- Delivery Time: 20 days for usual order, 7 days for stocked items
- Payment Terms: T/T, L/C, D/P
- Supply Ability: 1000pcs one month



Product Specification

- Highlight: GGG40 ductile iron swing check valve,
GGG50 ductile iron swing check valve,
GGG50 ductile iron check valves



More Images



for more products please visit us on piping-industry.com

Product Description

Iron Swing Check Valves Model No. CV-W-06

China ductile iron swing check valve manufacture supply GGG50/GG25 disc check valves with lever weight, DIN PN16.
Temperature: -30 ~+350

Request a quote

Tags:

Cast iron check valve
Ductile iron check valve
Bronze seat check valve
Metal seat check valve
Flanged check valve
Swing check valve
Disc check valve
Project check valve
Industry PN16 check valve
Check valve with lever weight

Quick Detail

BC bonnet cover Check Valve

| | |
|--|--|
| Material | Iron |
| Design standard | DIN 3202 F6 |
| Body material | Cast iron GG25 |
| Nominal diameter | 6" DN150 |
| Pressure | PN16 |
| End connection | RF. Flange EN1092-1 |
| Face to face | DIN3202 F6 EN558-1 Series 48 |
| Working temperature | -30 ~+350 |
| Test and inspection | API 598 |
| Connection | Flange ends conform to ASME B16.5 EN1092-1 |
| Epoxy powder coated inside and outside | 250Microns |
| FBE surface | 250Mincrons |

Product Range

Available Body Material: Cast Iron GG25, Ductile iron GGG40, GGG50
Available Disc Material: Ductile iron, Bronze
Optional Seat Ring: Brass, Bronze, SS304, SS316, EPDM
Optional Design: DIN /BS/ ANSI with difference Face to face length
Optional Ends: BS4504/EN1092-1 PN16/ ANSI B16.5 RF
Size Range: DN50-DN600 (2"-24")
Pressure Range: PN10, PN16, PN20(150LBS)
Optional surface color: RAL5002, RAL5015. RAL5005, red, black. Or customized

Performance

- 1.Iron Body with welded bronze seat ring.
- 2.Clear full opening waterway when disc is in fully open position.
- 3.Operating parts accessible through top opening.
- 4.Bronze bearings support stainless steel hinge pin and pressure sealed with O-rings.
- 5.Heavy ductile iron clapper arm.
- 6.Weights or spring lever may be used on either side for these types of check valves.
- 7.Heavy bronze disc stud is used on all types.
- 8.Iron discs for metal seated valves have bronze disc rings threaded into place.
- 9.Epoxy coated interior and exterior for corrosion resistance.

Application:

Pipeline for water, sewage, construction, petroleum, chemical, food, medicine, textile, power, shipbuilding, metallurgy and energy system



+8613292824811



sales@deyepiping.com



piping-industry.com

No. 368 Youyi St. Shijiazhuang, Hebei, China